

TB 34 MALAFASIZ BORU BÜKME MAKİNESİ

NONE MANDREL PIPE AND TUBE BENDING MACHINE



TEKNİK ÖZELLİKLER VE STANDART DONANIM

- Ø34 çapında ve 3 mm et kalınlığına kadar boruları 180°'ye kadar bükülebilir.
- Dijital açı göstergesi bulunmaktadır.
- İstenilen büküm açısı dijital göstergeden sınırlandırılabilir.
- Redüktör aktarmalı güç iletim sistemi.
- Sağlam çelik gövde.
- Geri esnemenen kaynaklanabilecek hatalı bükümleri önlemek için frenli motor.
- Üretim sahasında kolay taşınabilmesi için sökülebilir taşıma kolları.
- 1 set boru bükme kalıbı standart olarak dahildir.

ÖZEL DONANIM

- İstenilen ölçüde boru kalıbı seçenekleri

TECHNICAL SPECIFICATIONS AND STANDARD ACCESSORIES

- Capable of bending pipes with Ø34 diameter and 3 mm wall thickness up to 180°.
- Equipped with a digital readout.
- The desired bending angle can be limited via the digital readout.
- Gearbox-driven power transmission system.
- Durable steel body construction.
- Brake motor prevents bending errors caused by material springback.
- Detachable carrying handles for easy transport within the production area.
- Includes 1 set of pipe bending dies as standard.

OPTIONAL EQUIPMENTS

- Pipe die options available in custom dimensions.

MODEL		TB 34
Max Bükme Kapasitesi (D) Maximum Bending Capacity	mm	Ø34 x 3
Min Büküm Yarı Çapı (R) Minimum Bending Radius	mm	3xD (Boru çapı-Tube diameter)
Çıkış Devri Output Speed	rpm	1,9
Motor Gücü / Voltaj Motor Power / Voltage	kW / V	0,55 / 380
Ağırlık Weight	kg	90
Ölçüler Dimensions	mm	720x260x460

TB 42 MALAFASIZ BORU BÜKME MAKİNESİ

NONE MANDREL PIPE AND TUBE BENDING MACHINE



TEKNİK ÖZELLİKLER VE STANDART DONANIM

- Manuel ayarlanabilir açı ayarı
- Ø42mm x 3mm'ye kadar boru bükme kapasitesi
- Özel kalıp montajı için boş delikler
- Çelik kaynaklı gövde
- Ayarlanabilir hız
- Bir set boru bükme kalıbı dahildir
- Dijital gösterge

ÖZEL DONANIM

- İstenilen ölçülerde boru, profil veya dolu malzeme kalıpları

TECHNICAL SPECIFICATIONS AND STANDARD ACCESSORIES

- Manual adjustable angle switch
- Up to Ø42mm x 3mm tube bending capacity
- Free holes for assembly of the special tools
- Steel welded construction frame
- Adjustable speed
- One set of pipe bending tools included
- Digital readout

OPTIONAL EQUIPMENTS

- Sets of pipe, tube, section or bar rolls as required dimensions

MODEL		TB 42
Maks. basınç (200 bar) Max. pressure at 200 bars	ton	15
Yağ tankı kapasitesi Oil tank capacity	lt	15
Maksimum strok Maximum stroke	mm	150
Çalışma hızı Working speed	mm/s	20
Motor gücü Motor power	kW/V	1,1/ 380
Ağırlık Weight	kg	220
Uzunluk x Genişlik x Yükseklik Length x Width x Height	mm	450x1000x1000