


HPK 65 / HPK 40



HPK 65



HPK 40

MODEL		HPK 40	HPK 65
Üst mil çapı	Upper roll shaft	Ømm 40	60
Alt mil çapı	Bottom rolls shaft	Ømm 40	50
Vals topu çapı	Roll diameter	Ømm 137	180
Çalışma hızı	Working speed	m/min 7	5
Motor gücü	Motor power	kW/V 1,1/380	3/380
Uzunluk	Length	mm 1050	1200
Genişlik	Width	mm 530	850
Yükseklik	Height	mm 1250	1200
Ağırlık	Weight	kg 350	1000



TEKNİK ÖZELLİKLER VE STANDART DONANIM

- Çelik konstrüksiyon kaynaklı gövde
- Üç vals topu tahrikli
- Sertleştirilmiş ve taşlanmış miller
- Sertleştirilmiş standart vals topları
- Yatay ve dikey çalışma pozisyonu
- Standart vals takımı
- Gövdeden ayrı hareketli kumanda panosu
- 3 yöne hareketli mekanik yan dayamalar
- Frenli motor ile hassas büküm
- Dijital göstergeler (2 adet)

ÖZEL DONANIM

- NC Kontrol
- Hidrolik kılavuz silindireleri (2 Eksen)
- Spiral bükme vinci
- Özel profil valsı

TECHNICAL SPECIFICATIONS AND STANDARD ACCESSORIES

- Steel construction welded frame
- 3 rolls are powered
- Hardened and ground shafts made of high tensile special steel
- Horizontal and vertical working position
- Hardened standard rolls
- Mobile control panel
- 3 Axis mechanical lateral angle guide rolls
- Brake motor equipped for the precision bending
- Digital Read-Outs (2pcs)

OPTIONAL EQUIPMENTS

- NC Control
- Hydraulic lateral guide rollers (2 Axis)
- Spiral bending crane
- Special profile rolls

- ▶ Yatay Çalışma Pozisyonu
- ▶ Horizontal Working Position



- ▶ 2 Adet Dijital Göstergeler Standart
- ▶ 2 Pcs. Digital Read-out Standard

